

# **SN-ADR3116E2**

1080N 16CH 2HDD Hybrid DVR



#### **Key Features**


- Supports AHD/TVI/CVI/CVBS/IP video inputs
- VGA, HDMI video output
- Smart search / playback
- Response Time ≤0.2s
- Easy to use same Interface of GUI/WEB/Client
- Support more than languages
- Perfect protection circuit, unique triple watchdog function


## **Specification**

System	
Main Processor	Embedded processor
Operating System	Embedded LINUX
Video and Audio	
Analog Camera Input	16ch BNC
AHD Camera	1080N/720P @25/30fps
TVI Camera	1080N/720P @25/30fps
CVI Camera	1080N/720P @25/30fps
CVBS Camera	PAL/NTSC
IP Camera Input	16ch, each channel up to 1080P
Audio In/Out	6ch input, 1ch output, RCA
Two-way Talk	N/A
Display	
Interface	1 HDMI, 1 VGA
Interface	1 HDMI, 1 VGA  HDMI: 1920×1080,1440×900,1280×1024  VGA: 1920×1080, 1280×1024, 1280×720
	HDMI: 1920×1080,1440×900,1280×1024
Resolution  Multi-screen	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720
Resolution  Multi-screen Display	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720
Resolution  Multi-screen Display  Recording	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720 1/4/9/16
Resolution  Multi-screen Display  Recording  Resolution	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720 1/4/9/16
Resolution  Multi-screen Display  Recording  Resolution  Record Rate	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720 1/4/9/16 1080N, 720P, D1, CIF 1080N@15fps Main stream: 128Kbps~4096Kbps
Resolution  Multi-screen Display  Recording  Resolution  Record Rate  Bit Rate	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720 1/4/9/16 1080N, 720P, D1, CIF 1080N@15fps Main stream: 128Kbps~4096Kbps Sub stream: 16Kbps~1024Kbps
Resolution  Multi-screen Display  Recording  Resolution  Record Rate  Bit Rate  Record Mode	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720  1/4/9/16  1080N, 720P, D1, CIF  1080N@15fps  Main stream: 128Kbps~4096Kbps Sub stream: 16Kbps~1024Kbps  Manual, Event, Timer  Post-record: 30 ~ 60 sec
Resolution  Multi-screen Display  Recording  Resolution  Record Rate  Bit Rate  Record Mode  Record Interval	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720  1/4/9/16  1080N, 720P, D1, CIF  1080N@15fps  Main stream: 128Kbps~4096Kbps Sub stream: 16Kbps~1024Kbps  Manual, Event, Timer  Post-record: 30 ~ 60 sec
Resolution  Multi-screen Display  Recording  Resolution  Record Rate  Bit Rate  Record Mode  Record Interval	HDMI: 1920×1080,1440×900,1280×1024 VGA: 1920×1080, 1280×1024, 1280×720  1/4/9/16  1080N, 720P, D1, CIF  1080N@15fps  Main stream: 128Kbps~4096Kbps Sub stream: 16Kbps~1024Kbps  Manual, Event, Timer  Post-record: 30 ~ 60 sec  Ind Alarm  Recording, Buzzer, Push message, Pop up

Playback and Backup	
Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Playback Function	Play, Pause, Stop, Next Frame, Fast play, Slow Play, Layout, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB HDD
Network	
Interface	1 RJ-45 port (10/100Mbps)
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP
Max. User Access	Access 4 users
Smart Phone	iPhone, iPad, Android
Storage	
Internal HDD	2 SATA Ports, up to 8TB for each HDD
eSATA	N/A
Interface	
USB	2 ports (USB 2.0 x2)
RS232	N/A
RS485	1 Port, for PTZ Control
General	
Power Supply	DC12V/4A
Power Consumption	Max 10W (without HDD)
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	350mm(L)x305mm(W)x49mm(H)
Dimensions	

## Dimensions(mm)





### Rear Panel