

SN-NVR2632E4-P16

32CH 4HDD NVR with 16CH PoE



Key Features


- Up to 32ch IP cameras access
- Up to 12MP resolution recording
- 4 SATA hard disk each up to 12TB
- 1 RJ45 10M/100M/1000M network interface
- 16ch POE ports
- Support RAID 5/6/10
- Simultaneous HDMI&VGA up to 4K output
- Smart search & playback
- Support cloud upgrade


Specification

Video Input		
IP Camera Input	32 Channel	
Incoming Bandwidth	320Mbps	
Outgoing Bandwidth	320Mbps	
Video Output		
HDMI Output	3840×2160, 1920×1080,1440×900, 1280×1024	
VGA Output	1920×1080,1440×900, 1280×1024	
Different Source Output	Support	
Decoding Capacity	1ch 12MP, 4ch 8MP, 8ch 4MP, 16ch 1080P, 32ch 720P	
Dual Stream	Support	
Multi-screen Display	1st Screen: 1/4/8/9/16/32/36 2nd Screen: 1/4/8/9/16	
Recording		
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.	
Recording Mode	Manual, Schedule (Regular, Continuous), Event	
Trigger Events	Motion Detection, Video Loss, Alarm in	
Playback and Backup		
Sync Playback	16/9/4/1	
Search Mode	Time /Date, Alarm, Picture grid, Event	
Backup Mode	USB Device, Network, eSATA	
Network		
Interface	1 RJ-45 port (10/100/1000Mbps)	
PoE	16 Ports (IEEE 802.3af), 128W	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE	
Remote Users	8 users	
Smart Phone	iPhone, iPad, Android	
Interoperability	ONVIF, SDK	

Storage	
HDD	4 SATA Ports, up to 12TB for each HDD
eSATA	1 eSATA Port
Cloud Storage	Support
Disk Array	
Array Type	RAID 5, RAID 6, RAID 10
Interface	
Audio I/O	1/1
Alarm Input	2ch
Alarm Output	2ch
USB	3 ports (USB 2.0 × 2, USB3.0 × 1)
RS485	N/A
RS232	N/A
General	
Power Supply	AC100 ~ 240V
Power Consumption	< 15W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	440 × 368.3 × 70mm
Net Weight	4.65kg (without HDD)

Dimensions(mm)





Rear Panel

